

Akçaburgaz Mah. 3105. Sokak No: 8-12/1 Esenyurt/İSTANBUL +90 212 875 77 50 (3 lines) +90 212 875 08 22 info@anadolukimya.com www.anadolukimya.com

DOCUMENT NO:	TDS-WB.014
RELEASE DATE:	04.11.2017
REVISION NO:	03
REVISION DATE:	01.07.2021
PAGE NO:	1/1

# TECHNICAL DATA SHEET PS 05 CLEAR BASE - WB

# 1. ADVANTAGES

- It is a water-based printing paste, with ZDHC Level 3 certificate, used in textile printing applications to obtain opaque and colorful printing effect by coloring with FA-FR series pigments.
- High opacity
- · High elasticity
- · Soft touching effect
- · High dry-wet rubbing fastness
- · High washing fastness

# 2. PHYSICAL AND CHEMICAL PROPERTIES

Parameter	Unite	Limit	Standard
Appearance	-	Paste	In House
Color	-	Clear	In House
Odor	-	Characteristic	In House
Viscosity (25°C, 20 rpm)	cP	60000 - 80000	ISO 2884-2:2003
pН	-	7,5 - 8,5	ISO 19396-1:2017
Density (25 °C)	g/cm <sup>3</sup>	$1,09 \pm 0,05$	ISO 2811-1:2016

#### 3. APPLICATION

Parameter	Unite	Limit
Screen	Mesh	43-77
Squeegee	Shore	57-62
Squeegee Type	-	U
Curing Temperature	°C	160
Curing Time	minutes	Min.1,5
Number of Washes	times	5
Washing Temperature	°C	60

- · In order to have more color productivity and elasticity in the print of PS 05 Clear Base-WB, double print is advised with flash curing.
- · If necessary, PS 07/SP 240/GS 603/XP 50/ES 53 can be applied on dark colored fabrics as underbase.
- For polyester fabrics that cause dye migration, our SP 230 Anti Migration Base-WB product should be printed as underbase.
- · To reduce the viscosity SP 209 Regulator WB (1-3%) can be used. Never use water to reduce the viscosity.
- · Please stir the paste well before use. Do not use any additives that are not advised.
- · The screen should be cleaned with the water after use.
- To color PS 05 Clear Base-WB, FA series (1-5 %) or FR series (5-15 %) pigments are added.
- $\cdot$  Rubbing and washing tests should be applied 24 hours after curing.

# 4. PACKAGING INFORMATION

• The product is packed in 20 kg plastic white bucket with lid and handle & 30 or 60 kg open top plastic barrel with black plastic lid and steel securing clamp ring.

# 5. STORAGE & SAFETY

- · Keep containers dry and tightly closed. Store in a ventilated place between +5°C and +30°C (+41°F and +86°F) of temperature.
- It should be consumed within 12 months after the production date.
- It does not contain substances classified as harmful for inhalation and skin when used. For more information, please refer to the SDS.

# 6. ADDITIONAL INFO

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use.