

Akçaburgaz Mah. 3105. Sokak No: 8-12/1 Esenyurt/İSTANBUL +90 212 875 77 50 (3 lines) +90 212 875 08 22 info@anadolukimya.com www.anadolukimya.com

DOCUMENT NO:	TDS-WB.055	
RELEASE DATE:	01.03.2016	
REVISION NO:	04	
REVISION DATE:	11.02.2022	
PAGE NO:	1/1	

TECHNICAL DATA SHEET FA 3025 BLACK - WB

1. ADVANTAGES

- It is a water-based pigment dispersion used to color water-based printing pastes in textile printing applications.
- Providing high vivid colors
- High washing fastness

2. PHYSICAL AND CHEMICAL PROPERTIES

Parameter	Unite	Limit	Standard
Appearance	-	Liquid	In House
Color	-	Black	In House
Odor	-	Characteristic	In House
Viscosity (25°C, 50 rpm)	cP	Max 2000	ISO 2884-2:2003

3. APPLICATION

- **FA 3025 Black-WB** should be used at a rate of 1-5% in water-based printing pastes.
- In order to have better color productivity, double print is advised with flash curing.
- · Please stir it well before use. Do not use any additives that are not advised.
- The screen should be cleaned with the water after use.
- Rubbing and washing tests should be applied 24 hours after curing.

4. PACKAGING INFORMATION

• The product is packed in 5 kg plastic bucket with lid and handle.

5. STORAGE & SAFETY

- Keep containers dry and tightly closed. Store in a ventilated place between +5°C and +30°C (+41°F and +86°F) of temperature.
- It should be consumed within 12 months after the production date.
- · It does not contain substances classified as harmful for inhalation and skin when used. For more information, please refer to the SDS.

6. ADDITIONAL INFO

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use.